



精度等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			

8	Cover1	PA66	UL94V-0
7	Housing	PA66	UL94V-0
6	Spring	Stainless steel	
5	Pin	Copper	Sn Plated
4	Cover2	PA66	UL94V-0
3	Side Housing2	PA66	UL94V-0
2	Middle Housing	PA66	UL94V-0
1	Middle Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级	III/3	III/2	II/2
污染度/Pollution Degree	/	400/20	/
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	4
额定脉冲电压/Rate Impulse Voltage(KV)	/	/	/
额定范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5/22~14		
间距/Pitch(mm)/线长范围/Poles	7.5/N=02~12P		
剥线长度/Stripping length(mm)	9~10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	PANTONE 7534u		

MATERIAL: /
SURFACE: /

MAT NO.: /
STATUS: /
NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
宁波高松电子有限公司

APPD: /
CHKD: /
DRAWING NO.: 8EDGKRMA-7.5-C01

DRAFT: CenX 2020.06.10
TYPE: CUSTOMER DRAWING
SCALE: 2:1
REV T0
1/1

REV	ECN	DESCRIPTION	DRAFT	DATE