



Print content with the name of the product

未注公差/General tolerances (mm)														0.1/10
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'

(Series No.) DT22M - MXD X / Y AC/DCZV

(Voltage grade):
AC/DC: 6/12/24/36/48/
110/220V
AC: 110/220/380V

(Color): RD: (Red)
GN: (Green)

(Contact form): 10: 1N0
01: 1NC
11: 1N01NC

(Type of actuator): MRD: Mushroom reset indicator
MLD: Mushroom lock indicator

ITEM	NAME OF PART	MATERIAL	NOTES
4	Button head	/	/
3	Holding screw	/	/
2	Resistance module	/	/
1	Contact module	/	/

使用温度范围/Operating temperature (°C)	-25~+55(无冰冻)
使用湿度范围/Operating humidity(%RH)	45~85
接触电阻/Contact resistance(mΩ)	≤50
绝缘电阻/Insulation resistance(mΩ)	≥100
工频耐压/Power frequency withstand voltage	1890VAC/50Hz/60s
耐振动性/Vibration resistance	振幅约1.0mm/50Hz
耐冲击性/Shock resistance	>10g
机械寿命/Mechanical life	≥200万次
电气寿命/Electrical life	≥20万次
接线/Connection	螺钉连接, 线直径2x1.5mm 最大界限插片 6.3x0.8mm
符合RoHS环保要求/Conform to RoHS	Yes
标准颜色编号/Standard color number: PANTONE / RAL	/

DEGSON		MATERIAL:	SURFACE/COLOR:
APPD: 李根芳	2022.10.12	MAT NO./REV: / 00	MAT STATUS: 小批量
CHKD: 马恩开	2022.10.12	NAME	
DRFT: 马恩开	2022.10.12	DT22M-MXD _X /YAC/DCZV	
DRAWING NO.	TYPE	DRAWING STATUS	SCALE
200118621	CUSTOMER DRAWING	work	1:1
SHEET		1/1	

REV	ECN	DESCRIPTION	DRFT	DATE
00		New Drawing	马恩开	2022.10.12

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in general. All rights reserved for patent. Utility model or design registrations. 除专利等权利外, 本公司保留对本文件的所有权利。未经授权, 禁止复制或传播本文件内容。未经许可, 不得复制或传播本文件内容。