



公差/General tolerances(mm)	0.1/10
0	~
>3	~
>6	~
>10	~
>18	~
>30	~
>50	~
>80	~
>120	~
>180	~
>250	~
>315	~
>400	~
>500	~
>500	~
±0.12/±0.18/±0.22/±0.26/±0.31/±0.37/±0.57/±0.80/±0.93/±1.05/±1.15/±1.50/±2.20/±2.50	±7

ITEM	NAME OF PART	MATERIAL	NOTES
4	Short Pin	Copper	Sn plated
3	Long Pin	Copper	Sn plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL Standard	B	C	D
额定电压/Rated Voltage(V)	300/15	/	300/10
额定电流/Rated Current(A)	300/15	/	300/10
IEC 标准/IEC Standard			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)	/	320/10	/
额定脉冲电压/电压/Rate Impulse Voltage(KV)	/	4	/
间距/Pitch(mm)/线数范围/POes	5.08/N=04~48P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		

<b>DIASON</b>		SURFACE/COLOR:	
MAT NO./REV:	/ 00	MAT STATUS: 批量	

APPR: 兰春华	2024.04.09	NAME	2PDCRH-5-08-XXP-1Y-00A&Z(H)
CHKD: 李耀志	2024.04.01	DRAWING NO.	200019537
DRAFT: 方哲建	2024.04.01	TYPE	CUSTOMER DRAWING
DATE	2024.04.01	DRAWING STATUS	已发布
DRFT	方哲建	SCALE	2:1
DESCRIPTION	1X 标准IEC电源插座200系列为0A	SHEET	1/1
EON			
REV	02		