

## Overview

### Product information



## RM-EBBM-2003-M-25060000001

Right angle plug with direct plug in and out, rated current:20A; Rated voltage:110V DC; Withstand voltage:500V AC; Insulation resistance > 100M Ω; Protection grade meet IP67 when mated; Mechanical life ≥ 3000 times; Pull out force > 20N; Operating temperature: - 40 ~ 105 °C; Salt spray resistance : 72h; Flame retardant grade:UL94-v0; Environmental protection:RoHS. Color: lock ring - blue.

### Product advantages

- ☑ Fast direct plug connection
- ☑ After plugging in place, it has auditory and visual feedback
- ☑ High plug life
- ☑ Beautiful appearance, more in line with human functional design

### Product certification

# RoHS

## Technical data

### Product drawing

### 3D model

□

### Marking

classification	Insert
Series	DD
	DE
	DM

### technical parameter

insulation resistance	≥100MΩ
-----------------------	--------

Mechanical life	≥3000次
-----------------	--------

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	3A
	10A
	6B
	10B
	16B
	24B
	32B
Number of positions	48B
	4
	2

Environmental parameters

Degree of protection	MatchingIP67
----------------------	--------------

wire rod

Adapter wire range	6.1~6.6mm
--------------------	-----------

Accessories

Business data

Order number	25060000001
Packing unit	
Minimum order quantity	

Products weight (without packaging)	
-------------------------------------	--