

Overview

Product information



RM-EBBL-2105-M-25050000002

Right angle plug with direct plug in and out, rated current:50A; Rated voltage:110V DC; Withstand voltage:500V AC; Insulation resistance > 100M Ω; Protection grade meet IP67 when mated; Mechanical life ≥ 3000 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 ℃; Salt spray resistance : 72h; Flame retardant grade:UL94-v0; Environmental protection:RoHS. Color: lock ring - blue.

Product advantages

- ☑ Fast direct plug connection
- ☑ After plugging in place, it has auditory and visual feedback
- ☑ High plug life
- ☑ Beautiful appearance, more in line with human functional design

Product certification

RoHS

Technical data

Product drawing

3D model

□

Marking

classification	Insert
Series	DD
	DDD
	DM

technical parameter

insulation resistance	≥100MΩ
-----------------------	--------

Mechanical life	≥3000次
-----------------	--------

versions

Connection method	Screw connection
Female/Male	Male
Dimension	3A
	32A
	6B
	10B
	16B
	24B
	32B
	48B
Number of positions	1 module
	3
	2
	1

Environmental parameters

Degree of protection	MatchingIP67
----------------------	--------------

Accessories

Business data

Order number	25050000002
Packing unit	
Minimum order quantity	

Products weight (without packaging)	
-------------------------------------	--