

### Overview

#### **Product information**



# DG103-5.08-10040004776

PCB terminal blocks,Rated current:24A,Rated voltage (III/2) 250V,Cross section:2.5mm²,pitch:5.08mm,connector method:Screw connector with tension sleeve,Color:green,Contact surface :Tin

### Product advantages

- $\ensuremath{\square}$  Universal installation method to ensure a high degree of flexibility in device design
- ☑ 45° connection can realize multi-row layout on PCB
- ☑ Different poles can be combined through the side lock

#### Product certification



Technical d	lata		
Product d	lrawing		

3D model

### Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

### Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	24~12AWG
Torque	0.5N.m
Strip length	7mm

## Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

## Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	250V
Rated current	24A
Rated voltage(III/2)	400V
Rated voltage(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

# Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

## Material data

Environmental items	Compliant with REACH/RoHS	
Contact material	Copper alloy	
Contact point metal surface	tin-plated	
Insulation Materials	PA66	
Insulating material group	I	
Flammability rating	UL94V-0	
Mechanical tests		
Test Specification	IEC60947/UL1059	
Environmental data		
Ambient temperature (operation)	-40℃~105℃(depending on derating curve)	

ol	
screwdriver	0.6x3.5mm,Slotted screwdriver
Operating tool	
ccessories	
Coding strip	1
Marking strip	
Bridge	1
Other	
ccessories	
Coding strip	1
Bridge	
Marking strip	1

Tool		
Operating tool	1	
Screwdriver	0.6x3.5mm, Slotted screwdriver	

Business data		
Order number	10040004776	
Packing unit	400	
Minimum order quantity		
Products weight (without packaging)	2.73	