

Product information	
	ESS-150A-35-C-OR-90-20160003070 Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 35 mm ² , Rated voltage: 1500V, Rated current: 150 A, Connection method: Crimp, Contact type: Needle
Product advantages	
 Exclusive patents IP67 protection With safety locking latch The plug can rotate 360°after assemb The socket is with hand-proof protection With color-coded and mechnism-coded 	on
Product certification	
echnical data	
Product drawing	
Product drawing	
3D model	
3D model	
3D model	Crimp
3D model Wiring data	Crimp
3D model Wiring data Wiring mode	IP67
3D model Wiring data Wiring mode Environment condition	
3D model Wiring data Wiring mode Environment condition Protection grade (pair plug)	IP67 -40°C ~ +125°C
3D model Wiring data Wiring mode Environment condition Protection grade (pair plug) Ambient temperature (operation)	IP67 -40°C ~ +125°C

Plugging times	100
Pullout force	>10N
echanical properties	
Insertion force	< 100N
tandards and specifications	
Standard/Specification	UL4128
laterial data	
Insulating material	Nylon
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Sealing ring material	Silicone
Contact material	Copper alloy
Shell color	Orange
Flammability rating	UL94V-0
lectrical parameters	
Pollution level	3
Rated current	150A
	UL DC1500V
Insulation resistance	>5000MΩ
Contact resistance	≤0.5mΩ

Accessories

Business data

Order number

20160003070

Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	44.32