

Product information D-WS6-SD-11060000123 End cover, Wildh: 4 mm, Color: gray Product advantages Product contification Product contification Technical data Product drawing Technical data Product drawing Statistion Materials PA Gray Overview Statistion Materials PA Flame retardant grade, in line with U. 94 V0 Gray Duransion distint fungerature (operation) 4rmn Holph distint fungerature (operation) 40 °c ~ 105 °C (depending on derating curve) Stewironmental conditions Provious colspan="2">Stewironmental conditions Stewironmental conditions	Dverview		
End cover, Width: 4 m. Color: gray Product advantages Product certification Product certification Terdicat drawing Forduct drawing Product drawing Product drawing Product drawing Forduct drawing Product drawing Forduct drawing Product drawing Sourciew Parameter of the state of the s	Product information		
Product certification Flame related at a Product drawing 3D model 3D model Overview Insulation Materials PA Flame relatdant grade, in line with UL 94 V0 color Gray Dimension Vu width 4mm Height 36.8mm length 46mm Environmental conditions 40 °C ~ 105 °C (depending on derating curve) Ambient temperature (operation) -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%			
Technical data Product drawing 3D model 3D model Overview Insulation Materials PA Insulation Materials PA Flame retardant grade, in line with UL 94 V0 color Gray Dimension View width 4mm Height 36.8mm Iength 46mm Environmental conditions -40 °C ~ 105 °C (depending on derating curve) Ambient temperature (operation) -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	Product advantages		
Product drawing SD model SD model SU model Insulation Materials Insulation Materials Flame retardant grade, in line with UL 94 ofor ofor ofor with Height ingth Height Anbient temperature (operation) Anbient temperature (operation) Standard School (standard)	Product certification		
3D model Coerview Finalation Materials PA Flame retardant grade, in line with UL 94 00 color Col	Fechnical data		
verview Insulation Materials PA Flame retardant grade, in line with UL 94 V0 color Gray color Gray billmension 4mm Height 36.8mm length 4mm Environmental conditions 40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	Product drawing		
Overview PA Insulation Materials PA Flame retardant grade, in line with UL 94 00 color Gray Dimension Frame width Amm Height 36.8mm Iength 46mm Evironmental conditions 40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	3D model		
Insulation Materials PA Flame retardant grade, in line with UL 94 V0 color Gray Dimension Virth width 4mm Height 36.8mm length 46mm Environmental conditions -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%			
Flame retardant grade, in line with UL 94 V0 color Gray Dimension width 4mm Height 36.8mm length 46mm Environmental conditions Ambient temperature (operation) Ambient temperature (operation) -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	Overview		
color Gray Dimension 4mm width 4mm Height 36.8mm length 46mm Environmental conditions 40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	Insulation Materials		PA
Line Image: Constraint of the second of	Flame retardant grade, in line with UL 94		V0
width 4mm Height 36.8mm length 46mm Environmental conditions Ambient temperature (operation) -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	color		Gray
Height 36.8mm length 46mm Environmental conditions -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	Dimension		
length 46mm Environmental conditions -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	width		4mm
Environmental conditions Ambient temperature (operation) -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	Height		36.8mm
Ambient temperature (operation) -40 °C ~ 105 °C (depending on derating curve) Relative humidity (storage/transport) 25%~75%	length		46mm
Relative humidity (storage/transport) 25%~75%	Environmental conditions		
	Ambient temperature (operation)		-40 °C ~ 105 °C (depending on derating curve)
Ambient temperature (storage / transport) -25°C~60°C	Relative humidity (storage/transport)		25%~75%
	Ambient temperature (storage / transport)		-25°℃~60 °℃

Environmental protection	
RoHS	No excessive harmful substances
REACh SVHC	Lead 7439-92-1

Accessories

Business data

Order number	11060000123
Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	3.408