

Overview

Product information

**Relay module-DM72-RMUS-08-PN-1-44-01A(H)-30030000034**

Subminiature Relay Module,with relay Socket ,16 relays can be installed,with relay Socket,with indicator light,Honfa relay,PNP or NPN signal can be input

Product advantages

- ☑ Each signal channel and power supply voltage have LED status indicators
- ☑ Pluggable subminiature relay, with a set of normally open contacts, one-to-one output at the output
- ☑ Suitable for NPN, PNP controller
- ☑ Freewheeling diode for each signal path

Product certification

Technical data

Product drawing

3D model

□

Overview

Installation location	Arbitrary
Number of channels	8
Shell Insulation Materials	PVC/PA66
color	green

Dimension

width	90mm
Height	60mm
length	60mm

Enter technical data

Rated input voltage	24VDC
Input voltage range relative to UN	0.9....1.1
protected name	Polarity protection
Protection circuits/components	Polarity Protection Diode
Status display/channel	green

Export technical data

contact type	1NO
Maximum switching voltage	240VAC 30VDC
Limit continuous current	5A
Fault monitoring (open circuit/short circuit)	no

output connection data

connection name	output
Connection method	screw connection
Stripping length	6-7mm
thread	M3
connection volume	1
number of digits	16
Hard conductor cross section	1.0 ... 2.5mm ²
Flexible conductor cross section	1.0 ... 2.5mm ²
Connectable guide cross section AWG	28...12AWG

Enter connection data

connection name	enter
Connection method	screw connection
Stripping length	6-7mm
thread	M3

connection volume	1
number of digits	10
Hard conductor cross section	1.0 ... 2.5mm²
Flexible conductor cross section	1.0 ... 2.5mm²
Connectable guide cross section AWG	28...12AWG

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Accessories

Business data

Order number	30030000034
Packing unit	4
Minimum order quantity	4
Products weight (without packaging)	128