

| Overview | | | | |
|--|------------------------------|--|--|--|
| Product information | | | | |
| | | 5-92116900098 le pins,Adapter wire specification0.75mm² | | |
| Product advantages | | | | |
| ☑High-precision turning process, sta ☑Gold-plated and silver-plated are a ☑Comprehensive products, resistant | vailable, suitable for diffe | rent environmental requirements; | | |
| Product certification | | | | |
| | | | | |
| Technical data | | | | |
| Product drawing | | | | |
| | | | | |
| 3D model | | | | |
| Marking | | | | |
| classification | | Contact | | |
| Series | | 10A | | |
| Contact type | | Crimping contact | | |
| versions | | | | |
| Female/Male | | Male | | |
| manufacturing technique | | Turning | | |
| Material characteristics | | | | |
| RoHS | | Comply with RoHS exemptions | | |
| Material | | Copper alloy | | |
| Plating material | | Silver plated | | |

| Standards | | |
|---|----------------------|--|
| Connection meets standards | EN 60664-1 IEC 61984 | |
| Fechnical specification | | |
| Conductor cross sections (mm ²) | 0.75mm ² | |
| Conductor cross sections(AWG) | 18AWG | |
| Working current | ≤10A | |
| Contact resistance | ≤3mΩ | |
| Plating Thickness | ≥2µm | |
| Temperature range | -40°C~+125°C | |
| Strip length | 8mm | |
| working life-mating cycles | ≥500 | |

Accessories

Business data

| Order number | 92116900098 |
|-------------------------------------|-------------|
| Packing unit | 100 |
| Minimum order quantity | 100 |
| Products weight (without packaging) | 0.6404 |