

Overview

Product information



D32A-SF-4g-CV-PG21-21010000616

32A Lower base,Four levers,back cover ,side entry,PG21 Thread hole,Wear protective cover

Product advantages

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;

☑Various installation methods and outlet directions to meet on-site wiring requirements;

 $\ensuremath{\square}$ Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

Technical data

Product drawing

3D model

Marking

| classification | Upper Housing/base |
|----------------|-------------------------|
| Series | A |
| Туре | Surface mount base |
| Description | With plastic dust cover |
| Specification | Low structure |

versions

| Dimension | 32A |
|----------------------|-------------|
| locking Category | Double lock |
| Thread specification | 1x PG21 |

Material characteristics

| Flammability rating | V-0 |
|-------------------------------|--------------------------|
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey (RAL 7037) |
| Material (seal) | NBR |

Technical specification

| Limiting temperatures | -40℃~+125℃ |
|-----------------------|------------|
| IP class | IP65 |

Accessories

Business data

| Order number | 21010000616 |
|-------------------------------------|-------------|
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 388 |