


## Overview

### Product information



## DA-010-FC-21020000104

Heavy-duty insert, Number of contacts: 10+PE, Dimension: 10A, Rated voltage :250V, Rated current: 16A, Female insert, Crimping connector

### Product advantages

- ☑Crimping connection technology, high wiring efficiency
- ☑Suitable for vibration occasions;
- ☑The wiring harness can be pre-installed;
- ☑Choose contacts with different wire diameters and coatings;
- ☑High-density pins, saving installation space;
- ☑With grounding protection.

### Product certification



## Technical data

### Product drawing

### 3D model



### Marking

classification	Insert
Series	DA

### versions

Connection method	Crimping connection
Female/Male	Female
Dimension	10A
Number of positions	10

PE Contacts	Yes
-------------	-----

Material characteristics

Material（insert）	Polycarbonate（PC）
Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	250V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7.5mm
Conductor cross sections（mm <sup>2</sup> ）	0.14-4.0mm <sup>2</sup>
Conductor cross sections(AWG)	26-12AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessories

Accessories

Crimping tool Removal tool	/
----------------------------	---

Business data

Order number	21020000104
Packing unit	100
Minimum order quantity	5
Products weight (without packaging)	30