

Overview

Product information



SD-M12B-05P-MM-SH8001-20030001190

Sensor/Actuator Female socket, M12, Coding A, Front panel installation/PG9 Thread mounted, Soldering cup

Product advantages

☑ Sealing optimization, protection level up to IP68

☑Meet the harsh environment

☑Suitable for various occasions connection technology

 $\ensuremath{\square}$ Compatible with the international and domestic same series products

Product certification



c SNOW ROHS REACH C SNOW



Technical data

Prod	luct	dra	wina
FIUU	ucı	ula	wiiiu

3D model

Environmental conditions

Ambient temperature	-40℃105℃
IP class	IP68

General parameters

Rated current	4A
Kaleu current	60V
Number of potentials	5
Insulation resistance	≥ 100 MΩ
Error-proof coding	B-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board
Matarial	

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Accessories

Accessories

Sealing cap CAP-M12-FP-8002

Business data

Order number	20030001190
Packing unit	1
Minimum order quantity	100
Products weight (without packaging)	1

