

## Overview

### Product information



## DG504-5.08-10040000543

PCB terminal blocks, Rated current: 20A, Rated voltage (III/2) 400V, Cross section: 0.2~2.5mm<sup>2</sup>, pitch: 5.08mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

### Product advantages

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ 45° connection can realize multi-row layout on PCB
- ☒ Different poles can be combined through the side lock

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.2~2.5mm<sup>2</sup>

Conductor cross section flexible

0.2~2.5mm<sup>2</sup>

AWG

30~12AWG

Torque

0.5N.m

Strip length

11mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	250V
Rated current	20A
Rated voltage(III/2)	400V
Rated voltage(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C(depending on derating curve)
---------------------------------	--

### Accessories

#### Accessories

Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/

#### Tool

Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

### Business data

Order number	10040000543
Packing unit	150
Minimum order quantity	30

Products weight (without packaging)	4.7
-------------------------------------	-----