

Dverview		
Product information		
CC	PCB spring terminal	.0-DA-10060001988 blocks,Rated current:76A.Rated voltage :10.0mm,Color:green,Contact surface :Tin
Product advantages		
 PUSH-IN connection technolog Different poles can be combin Universal installation method, 	ed through the side lock	3
Product certification		
	EAC	
Product drawing 3D model Processing notes		Wave soldering/manual soldering
Connection capacity		
Conductor cross section solid		0.2~16mm²
Conductor cross section flexibl	e	0.2~16mm ²
AWG		20~4AWG
Strip length		17mm
Electrical parameters UL		
Rated voltage (B)		600V
Rated voltage (C)		600V

Rated voltage (D)	600V
Rated current (B)	70A
Rated current (D)	5A
Rated current (C)	70A

Electrical parameters IEC

Rated voltage	1000V
Rated voltage(III/3)	1000V
Rated current	76A
Rated voltage(III/2)	1000V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	2
Pluggable or not	no
Number of rows	1
Material data	
Environmental items	Compliant with REACH/RoHS

Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ι
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories		
Accessories		
Coding strip	1	
Bridge	1	
Marking strip	1	
Others	1	
Tool		
Operating tool	1	
Screwdriver	1	

Business data	
Order number	10060001988
Packing unit	165
Minimum order quantity	30

Products weight (without	
packaging)	