

Overview				
Product information				
	Pluggable terminal bl	5.0-10010003732 locks,Rated current:20A.Rated voltage 6.0mm,Color:green,Contact surface :Tin		
Product advantages				
<ul> <li>Adapt to multi-type plugs, device of</li> <li>Keying parts can be installed</li> <li>Universal installation method, suit</li> </ul>				
Product certification				
c <b>FN</b> <sup>®</sup> us				
Technical data				
Product drawing				
3D model				
0				
Connection capacity				
Conductor cross section solid		1.0~2.5mm²		
Conductor cross section flexible		1.0~2.5mm²		
AWG		28~12AWG		
Torque		0.8N.m		
Strip length		7mm		
Electrical parameters UL				
Rated voltage (B)		300V		
Rated voltage (D)		300V		
Rated current (B)		15A		

Rated current (D)	10A
lectrical parameters IEC	
Rated voltage	320V
Rated current	20A
Rated voltage(III/2)	320V
Rated power frequency voltage(1min)	2.5KV
em properties	
Connection direction	0°
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1
<i>I</i> aterial data	
Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66

 Insulation Materials
 PA66

 Insulating material group
 I

 Flammability rating
 UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C(depending on derating curve)

bol	
Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	Ι
ccessories	
Coding strip	2EDG-PWP
Bridge	DG019-5.0
Marking atrip	1
Marking strip	

Business data	
Order number	10010003732
Packing unit	100
Minimum order quantity	30
Products weight (without packaging)	4.25