


## Overview

### Product information



## 2EDGKAM-7.62-10010001890

Pluggable terminal blocks, Rated current: 10A. Rated voltage  
(III/2) : 400V, pitch: 7.62mm, Color: green, Contact surface : Tin

### Product advantages

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Universal installation method, suitable for various situations

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Connection capacity

|                                  |                        |
|----------------------------------|------------------------|
| Conductor cross section solid    | 1.0~2.5mm <sup>2</sup> |
| Conductor cross section flexible | 1.0~2.5mm <sup>2</sup> |
| AWG                              | 28~12AWG               |
| Strip length                     | 7mm                    |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 15A  |
| Rated current (D) | 10A  |

Electrical parameters IEC

|                            |      |
|----------------------------|------|
| Rated voltage              | 400V |
| Rated current              | 18A  |
| Rated voltage(III/2)       | 400V |
| Rated surge voltage(III/2) | 4KV  |

Item properties

|                      |                     |
|----------------------|---------------------|
| Connection direction | 90°                 |
| Connection method    | Screw connection    |
| Screwdriver          | Slotted screwdriver |
| screw thread         | M3                  |
| Pitch                | 7.62mm              |
| Number of potentials | 3                   |
| Pluggable or not     | Yes                 |
| Number of rows       | 1                   |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | Copper alloy              |
| Contact point metal surface | tin-plated                |
| Contact zone metal surface  | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

Ambient temperature (operation)

-40°C~105°C(depending on derating curve)

Accessories

Business data

|                                     |             |
|-------------------------------------|-------------|
| Order number                        | 10010001890 |
| Packing unit                        | 100         |
| Minimum order quantity              | 30          |
| Products weight (without packaging) | 7.754       |